DESIGNED SPECIFICALLY FOR THE AMBULATORY PATIENT

Specifically designed for the ambulatory patient, the ActiV.A.C.® Negative Pressure Wound Therapy System is a lightweight, portable system that combines enhanced technology with easy-to-use features to facilitate the mobility of patients who may benefit from V.A.C.® Therapy.

Easy to Use Therapy Unit

- Simple touch-screen controls
- Quick release 300mL canister
- Single-touch therapy on/off
- Intuitive menus simplify therapy programming and operation
- Common touch-screen interface with InfoV.A.C.® Therapy System reduces training time and eases patient transitions



SensaT.R.A.C.™ Technology and Pad

- Alarm differentiation for easier troubleshooting
- Surface designed with patient comfort in mind
- Flexible pad easily conforms to patient contours
- Low profile design fits under clothing



Seal Check[™] Feature

- Provides instant feedback to help identify leaks
- Helps ensure accurate seals
- Easy troubleshooting for patients may reduce unscheduled caregiver visits



Therapy History Report

 Allows clinicians to monitor and track therapy settings, alarm history, therapy dates and times, dressing and canister changes and record the number of pieces of foam used



Settings Guide

- Aligned with V.A.C.® Therapy Clinical Guidelines
- Preset therapy settings by wound type eases setup
- Step-by-step guide simplifies setup for infrequent users





ActiV.A.C.® Therapy System Specifications

ActiV.A.C.® Therapy System Part Number#340000

Weight: 2.4 lbs (1.08 kg) with an empty canister

(19.3 x 15.2 x 6.4cm)

Battery Type: Lithium ion rechargeable battery

Recharging Time: 6 hours to reach full charge from a

completely discharged state

Canister Size: 300mL

Therapy Delivery Modes: Continuous or Intermittent

Intensity Settings: Low, Medium, High

Therapy Pressure Options: Negative Pressure: -25mmHg

through -200mmHg (-3.3kPa

to -26.6kPa)

Carrying Case: The black nylon design allows for full

touch screen navigation, battery charging, and tubing storage without removing the ActiV.A.C.® Therapy Unit from the case. The case has an adjustable, padded strap and a belt loop that allows the unit to be worn

in multiple orientations.

Electrical Data

External Power Supply Input: 100-240 VAC .72 A @ 115 VAC 47-63 Hz

External Power Supply Output: 12 V. 3.3 A

Patient & Enclosure Leakage Current: <100 Microamps

IEC Classification

- Type B, Applied Part, Class II, IPX0

- Equipment not suitable for use in presence of flammable anesthetic mixture with air, oxygen or nitrous oxide

Storage Conditions

Temperature Range: -4°F (-20°C) to 140°F (60°C) Relative Humidity Range: . . . 0-95% non-condensing

Operating Conditions

Temperature Range: 41°F (5°C) to 104°F (40°C) Relative Humidity Range: . . .0-95% non-condensing Altitude Range: 0 to 14,000 feet (0 to 4267 m) Optimum Performance: 0 to 8,000 feet (0 to 2438 m)



For more information about V.A.C.® Therapy call KCI toll free at **1-800-668-5403** or visit us online at **www.kci-medical.ca**

NOTE: Disposable components of the V.A.C.® (Vacuum Assisted Closure®) Therapy System, including the foam dressing (i.e., V.A.C.® GranuFoam™, V.A.C.® GranuFoam Silver™, or V.A.C.® WhiteFoam Dressing), tubing and drape are packaged sterile and are latex-free. V.A.C.® Therapy Unit canisters are packaged sterile or fluid path sterile and are latex free. All disposable components of the V.A.C.® Therapy System are for single use only. To help ensure safe and effective use, the V.A.C.® GranuFoam™, V.A.C.® GranuFoam Silver™ and V.A.C.® WhiteFoam Dressings are to be used only with V.A.C.® Therapy Units.

NOTE: Specific indications, contraindications, warnings, precautions and safety information exist for KCI products and therapies. Please consult a physician, product manual, product labeling and V.A.C.® Therapy Clinical Guidelines for important indications, contraindications, warnings, precautions, safety information and operating instructions prior to use. This material intended for healthcare professionals only.



